



SPECIFICATIONS

ALL DIMENSIONS IN MILLIMETRES.

CONCRETE:

35 MPa @ 28 DAYS,
6% AIR ENTRAINMENT IN ACCORDANCE
WITH CSA A23.1 MOD-M90

REINFORCING:

IN ACCORDANCE WITH CSA A23.1-M90
ALL REINFORCING STEEL HAS 30mm MIN. COVER

WEIGHT:

WALLS -1512 KG/V.M.
MONOBASE -264 KG

NOTES:

PRODUCT MANUFACTURED TO O.P.S.D. 705.040 TYPE B.

MANUFACTURED IN ACCORDANCE WITH OPSS 1351.

REINFORCING DETAILS AVAILABLE UPON REQUEST.

ALL PIECES INCLUDE SWIFT LIFT LIFTING ANCHORS.

OPTIONS AVAILABLE UPON REQUEST INCLUDE:

- PIPE GASKETS
- CAST-IN SUB-DRAIN COUPLERS
- DRILLED WEEP HOLES.

GRATE		DIMENSIONS		
TYPE	SLOPE	A	B	C
C	2:1	1341	66	1055
C	3:1	1265	104	805
C	4:1	1237	118	680
B	6:1	1216	65	555
B	8:1	1210	65	493
B	10:1	1206	70	455
B	HOR	1200	73	305

600x1200mm DITCH INLET TYPE B (DI1200)



1645 SYDENHAM RD.
KINGSTON, ONT.

PHONE:
(800) 223-0012
1-613-546-6683

www.anchorconcrete.com