



SPECIFICATIONS

ALL DIMENSIONS IN MILLIMETRES.

CONCRETE:

35 MPa @ 28 DAYS,
6% AIR ENTRAINMENT IN ACCORDANCE
WITH CSA A23.1 MOD-M90

REINFORCING:

IN ACCORDANCE WITH CSA A23.1-M90
ALL REINFORCING STEEL HAS 30mm MIN. COVER

WEIGHT:

WALLS -1080 KG/V.M.
BASE -130 KG

NOTES:

PRODUCT MANUFACTURED TO O.P.S.D. 705.030.

MANUFACTURED IN ACCORDANCE WITH OPSS 1351.

REINFORCING DETAILS AVAILABLE UPON REQUEST.

ALL PIECES INCLUDE SWIFT LIFT LIFTING ANCHORS.

OPTIONS AVAILABLE UPON REQUEST INCLUDE:
PIPE GASKETS
CAST-IN SUB-DRAIN COUPLERS
DRILLED WEEP HOLES.

SLOPE OF GRATING	DIMENSIONS		
	A	B	C
2:1	675	50	760
3:1	645	65	610
4:1	625	75	530
6:1	605	85	455
8:1	605	85	418
10:1	605	85	395

600x600mm DITCH INLET (DI0600)



1645 SYDENHAM RD.
KINGSTON, ONT.

PHONE:
(800) 223-0012
1-613-546-6683

www.anchorconcrete.com