



SIDE SECTION  
1:40

END SECTION  
1:40

**2000 GALLON SEPTIC TANK (ST2000)**

**SPECIFICATIONS**

ALL DIMENSIONS IN MILLIMETRES.

**NOM. CAPACITY:**

2000 GALLONS (9092 LITRES) TO INVERT OF OUTLET.  
36.4 GALLONS/IN. VERTICALLY.  
6494 LITRES/M VERTICALLY.

**CONCRETE:**

45 MPa @ 28 DAYS,  
6% AIR ENTRAINMENT IN ACCORDANCE  
WITH CSA A23.1 MOD-M90

**REINFORCING:**

IN ACCORDANCE WITH CSA A23.1-M90  
ALL REINFORCING STEEL HAS 30mm MIN. COVER.  
REINFORCING DETAILS AVAILABLE UPON REQUEST.

**BAFFLES:**

PVC PLASTIC LOCKED INTO CONCRETE.

**INLET & OUTLET:**

LOW PRESSURE PIPE SEALS FOR  
51 (2"), 76 (3") OR 102 (4") PIPE  
(INVERT AT SAME ELEVATION).

**WEIGHT:**

BOTTOM	-6876 KG
TOP SLAB	-2395 KG

**NOTES:**

MANUFACTURED IN ACCORDANCE WITH OPSS 1351.

ALL PIECES INCLUDE SWIFT LIFT LIFTING ANCHORS.

VARIABLE OPENINGS IN TOP SLAB  
AVAILABLE UPON REQUEST.

MAX. BURIAL DEPTH: 610mm.  
DEEP BURIAL DEPTHS AVAILABLE UPON REQUEST.

REFER TO INSTALLATION GUIDELINES FOR TANKS.



1645 SYDENHAM RD.  
KINGSTON, ONT.

PHONE:  
(800) 223-0012  
1-613-546-6683

www.anchorconcrete.com